

Acriflex Rapido

Single-component, water-based liquid waterproofing (such as **Acriflex Rapido**) designed with the quick-drying technology. Resistant to washout 20 minutes after application, it is formulated with specific elastomeric resins that exploit air for a rapid drying. Suitable for waterproofing concrete roofs, terraces, balconies, eaves, foundation walls as well as interiors, for repairing existing bituminous membranes and for waterproofing under tiles, even in low temperature and high relative humidity conditions. Suitable for asbestos encapsulation in accordance with art. 2 of Ministerial Decree 20/08/1999 and subsequent amendments and UNI 10686. Minimum characteristics required: Water impermeability – test passed; Resistance to wash out – 20 min (up to +1 °C and H.R.% 98%); Break Elongation 160 ± 10%; Lead resistance 1.4 ± 0.5 MPa; Adhesion test by direct traction on concrete 0.536 N/mm²; Weathering Test 1680 hours (>10 years); Viscosity at 23°C is 20000 ± 5000 cPs; Dry extract 74 ± 2%.

DIASEN srl

Zona Ind. Berbentina, 5 60041 Sassoferrato (AN) - ITALY
Tel. +39 0732 9718 - Fax +39 0732 971899 - diasen@diasen.com - www.diasen.com
PARTITA IVA 01553210426 - R.E.A. Ancona n.150933
Reg.Imp. Ancona 01553210426 - Cap. Soc. €400.000,00 i.v.

