

Declaration of Performance 0068 – CPR – 023/2014 - DP012EN1442204

1. **Unique identification code of the product-type:** Oriplast Reflex
2. **Type, batch or serial number or any other element allowing identification of the construction product as required under Article 11(4):**
 Product name: Oriplast Reflex
 Production date and batch are printed on the package.
 Production plant: Diasen Srl - zona Ind.le Berbentina, 5 - 60041 Sassoferrato (AN)
3. **Intended use or uses of the construction product, in accordance with the applicable harmonized technical specification, as foreseen by the manufacturer:**
 Products and systems for the protection and restoration of concrete structures – Part 2 : Systems to protect concrete surfaces in accordance with UNI EN 1504-2.
 Intended use: products for protection of surfaces -coating. Intended employment:: control of damp and increase in resistivity
 Product used in buildings and civil engineer works.
4. **Name, registered trade name or registered trade mark and contact address of the manufacturer as required under Article 11(5):**
 Diasen Srl - zona Ind.le Berbentina, 5 - 60041 Sassoferrato (AN) – www.diasen.com
5. **Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2):**
 Not applicable.
6. **System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:**
 System 2+.
7. **In case of the declaration of performance concerning a construction product covered by a harmonized standard:**
 Istituto di Ricerche e Collaudi M. Masini - Identification number: 0068
 Has done:
 1. initial inspection of the production plant and production control;
 2. supervision, assessment and evaluation of plant production control. According to system 2+ and issued the certificate of conformity of the plant production control n. 0068-CPR-023/2014 del 31/03/2014.

8. Declared performance:

Essential Characteristics	Performance	Harmonized Technical Specification
Water vapour permeability	NPD	UNI EN ISO 7783
Capillary absorption and water permeability	NPD	UNI EN 1062-3
Adhesion test of straight traction	0,780 N/mm ² , break type A/B	UNI EN 1542
Reaction to fire	class B – s2, d0	UNI EN 13501-1
Dangerous substances	See the SDS	Regolamento CE n. 1272/2008


9. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 8. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by: Diego Mingarelli – Legal representative

Sassoferrato, 16/07/2014

R04_7.2_SGQA rev 0 del 30/06/2013


DiaSen srl
 Z. Ind.le Berbentina, 5
 60041 Sassoferrato (AN)
 P. IVA/C.S. 01553210426

 0068	 Zona Industriale Berbentina, 5 – 60041 Sassoferrato (AN) – Italy www.diasen.com										
<p style="text-align: center;">14 CPD – 023/2014 UNI EN 1504-2 ORIPLAST REFLEX</p> <p style="text-align: center;"><i>Products and systems for the protection and restoration of concrete structures – Part 2 : Systems to protect concrete surfaces</i></p> <table border="0" style="width: 100%;"> <tr> <td style="width: 60%;">Water vapour permeability</td> <td>NPD</td> </tr> <tr> <td>Capillary absorption and water permeability</td> <td>NPD</td> </tr> <tr> <td>Adhesion test of straight traction</td> <td>0,78 N/mm², break type A/B</td> </tr> <tr> <td>Fire resistance</td> <td>Class B – s2, d0</td> </tr> <tr> <td>Dangerous substances</td> <td>See the SDS</td> </tr> </table>		Water vapour permeability	NPD	Capillary absorption and water permeability	NPD	Adhesion test of straight traction	0,78 N/mm ² , break type A/B	Fire resistance	Class B – s2, d0	Dangerous substances	See the SDS
Water vapour permeability	NPD										
Capillary absorption and water permeability	NPD										
Adhesion test of straight traction	0,78 N/mm ² , break type A/B										
Fire resistance	Class B – s2, d0										
Dangerous substances	See the SDS										