

Declaration of Performance 0068 – CPR – 023/2014 - DP087EN1602404

1. **Unique identification code of the product-type:** Medium Paint
2. **Type, batch or serial number or any other element allowing identification of the construction product as required under Article 11(4):**
 Product name: Medium Paint
 Production date and batch are printed on the package.
 Production plant: Diasen Srl - zona Ind.le Berbentina, 5 - 60041 Sassoferrato (AN)
3. **Intended use or uses of the construction product, in accordance with the applicable harmonized technical specification, as foreseen by the manufacturer:**
 Products and systems for the protection and restoration of concrete structures – Part 2 : Systems to protect concrete surfaces in accordance with UNI EN 1504-2.
 Intended use: surface protection – coating. Humidity control and improved resistance. Product used in buildings and civil engineer works.
4. **Name, registered trade name or registered trade mark and contact address of the manufacturer as required under Article 11(5):**
 Diasen Srl - zona Ind.le Berbentina, 5 - 60041 Sassoferrato (AN) – www.diasen.com
5. **Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2):**
 Not applicable.
6. **System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:**
 System 2+.
7. **In case of the declaration of performance concerning a construction product covered by a harmonized standard:**
 Istituto di Ricerche e Collaudi M. Masini - Identification number: 0068
 Has done:
 1. initial inspection of the production plant and production control;
 2. supervision, assessment and evaluation of plant production control. According to system 2+ and issued the certificate of conformity of the plant production control n. 0068-CPR-023/2014 del 31/03/2014.

8. Declared performance:

Essential Characteristics	Performance	Harmonized Technical Specification
Vapour permeability value	$\mu = 689$	UNI EN ISO 7783
Capillary absorption and water permeability	NPD	UNI EN 1062-3
Adhesion test for direct traction	NPD	EN 1542
Reaction to fire	NPD	UNI EN 13501-1
Dangerous substances	Read the SDS	EC Regulation n. 1272/2008

9. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 8. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by: Diego Mingarelli – Legal representative
 Sassoferrato, 14/01/2016

R04_7.2_SGQA rev 0 del 30/06/2013

DiaSen srl
 Z. Ind.le Berbentina, 5
 60041 Sassoferrato (AN)
 P. IVA/C.F. 01553210426

 0068	 Zona Industriale Berbentina, 5 – 60041 Sassoferrato (AN) – Italy www.diasen.com										
<p style="text-align: center;">14 CPR – 023/2014 UNI EN 1504-2 MEDIUM PAINT</p> <p style="text-align: center;"><i>Products and systems for the protection and restoration of concrete structures – Part 2 : Systems to protect concrete surfaces</i></p> <table border="0"> <tr> <td>Vapour permeability value</td> <td>$\mu = 689$</td> </tr> <tr> <td>Capillary absorption and water permeability</td> <td>NPD</td> </tr> <tr> <td>Adhesion test for direct traction</td> <td>NPD</td> </tr> <tr> <td>Reaction to fire</td> <td>NPD</td> </tr> <tr> <td>Dangerous substances</td> <td>Read the SDS</td> </tr> </table>		Vapour permeability value	$\mu = 689$	Capillary absorption and water permeability	NPD	Adhesion test for direct traction	NPD	Reaction to fire	NPD	Dangerous substances	Read the SDS
Vapour permeability value	$\mu = 689$										
Capillary absorption and water permeability	NPD										
Adhesion test for direct traction	NPD										
Reaction to fire	NPD										
Dangerous substances	Read the SDS										