

DECLARATION OF PERFORMANCE

CPR-U132

DP013EN22050201

- 1. Unique identification code of the product-type: Floorgum Paint
- 2. Intended uses: Cementitious coating for intended use in concrete surface protection by moisture control and increasing resistivity methods.
- 3. Manufacturer: Diasen Srl zona Ind.le Berbentina, 5 60041 Sassoferrato (AN) www.diasen.com
- 4. Systems of AVCP: System 2+

System 4 (for reaction to fire)

- Harmonized standards: BS EN 1504-2:2004.
 Notified bodies: British Board of Agrément (BBA) No 0836.
- 6. Performances declared:

Essential characteristics	Performances
Water vapour permeability	μ = 689
Capillary absorption and permeability to water	NPD
Tensile adhesion strength after freeze-thaw cycles	NPD
Adhesion strength by pull-off test	NPD
Reaction to fire	Class B - s2, d0
Dangerous substances	See SDS

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by: **Diego Mingarelli (Legal Representative)** Sassoferrato, 22/11/2021

DiaSen srl Z. Ind.le Berbentina, 5 Sassofer ato (AN)



DIASEN srl Zona Ind. Berbentina, 5 60041 Sassoferrato (AN) - ITALY Tel. +39 0732 9718 - Fax +39 0732 971899 - diasen@diasen.com - www.diasen.com PARTITA IVA 01553210426 - R.E.A. Ancona n.150933 Reg.Imp. Ancona 01553210426 - Cap. Soc. €400.000,00 i.v.



UK CA 0836	Zona Industriale Berbentina, 5 – 60041 Sassoferrato (AN) – Italy www.diasen.com		
21 CPR–21/F517 BS EN 1504-2 : 2004 FLOORGUM PAINT Cementitious coating for intended use in concrete surface protection by moisture control and increasing resistivity methods			
Water vapour permeability		µ = 689	
Capillary absorption and permeability to water		NPD	
Tensile adhesion strength after freeze-thaw cycles		NPD	
Adhesion strength by pull-off test		NPD	
Reaction to fire		Class B - s2, d0	
Dangerous substances		See SDS	

DIASEN supplies the current annex along with the DoP to make the consultancy of the CE marking easier for the international clients. The enclosed CE marking can be slightly different compared to the one printed on the relevant packaging or documentation because of:

- graphic adaptations due to lack of space on the packaging or printing methods used,
- different language (the same packaging can be shared by several countries),
- the product is already in stock when the updating of the CE marking is implemented,
- printing mistakes.

DIASEN srl

Zona Ind. Berbentina, 5 60041 Sassoferrato (AN) - ITALY Tel. +39 0732 9718 - Fax +39 0732 971899 - diasen@diasen.com - www.diasen.com PARTITA IVA 01553210426 - R.E.A. Ancona n.150933

