

**Declaration of Performance**  
**1982 – CPR – 1223 – DP137EN20392200**

1. **Unique identification code of the product-type:** Acriflex Primer
2. **Type, batch or serial number or any other element allowing identification of the construction product as required under Article 11(4):**  
 Product name: Acriflex Primer  
 Production date and batch are printed on the package.  
 Production plant: Diasen Srl - zona Ind.le Berbentina, 5 - 60041 Sassoferrato (AN)
3. **Intended use or uses of the construction product, in accordance with the applicable harmonized technical specification, as foreseen by the manufacturer:**  
 Products and systems for the protection and restoration of concrete structures – Part 2 : Systems to protect concrete surfaces in accordance with EN 1504-2:2004.  
 Intended use: products for protection of surfaces - coating. Intended employment: control of damp and increase in resistivity.  
 Product used in buildings and civil engineer works.
4. **Name, registered trade name or registered trade mark and contact address of the manufacturer as required under Article 11(5):**  
 Diasen Srl - zona Ind.le Berbentina, 5 - 60041 Sassoferrato (AN) – www.diasen.com
5. **Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2):**  
 Not applicable.
6. **System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:**  
 System 2+.
7. **In case of the declaration of performance concerning a construction product covered by a harmonized standard:**  
 ABICert - Identification number: 1982  
 Has done:
  1. initial inspection of the production plant and production control;
  2. supervision, assessment and evaluation of plant production control. According to system 2+ and issued the certificate of conformity of the plant production control n. 1982-CPR-1223 del 03/08/2018.



**8. Declared performance:**

Essential Characteristics	Performance	Norm
CO <sub>2</sub> permeability	NPD	EN 1504-2:2004
Water vapour permeability	Class I	
Capillary absorption and water permeability	< 0,1 kg*m <sup>-2</sup> *h <sup>-0,5</sup>	
Direct traction adhesion test	> 0,8 N/mm <sup>2</sup>	
Fire reactions	NPD	
Dangerous substances	Read the SDS	

9. **The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 8. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.**  
 Signed for and on behalf of the manufacturer by: Diego Mingarelli – Legal representative  
 Sassoferrato, 04/09/2018

  
 DiaSen srl  
 Z. Ind.le Berbentina, 5  
 60041 Sassoferrato (AN)  
 P. IVA/C.F. 01553210426



 1982	 GREEN BUILDING FUTURE Zona Industriale Berbentina, 5 – 60041 Sassoferrato (AN) – Italy <a href="http://www.diasen.com">www.diasen.com</a>												
<p style="text-align: center;"><b>18</b>  <b>1982 - CPR – 1223</b>  <b>EN 1504-2:2004</b>  <b>ACRIFLEX PRIMER</b></p> <p style="text-align: center;"><i>Products and systems for the protection and restoration of concrete structures – Part 2 : Systems to protect concrete surfaces</i></p> <table border="0"> <tr> <td>CO<sub>2</sub> permeability</td> <td>NPD</td> </tr> <tr> <td>Water vapour permeability</td> <td>Class I</td> </tr> <tr> <td>Capillary absorption and water permeability</td> <td>&lt; 0,1 kg*m<sup>-2</sup>*h<sup>-0,5</sup></td> </tr> <tr> <td>Direct traction adhesion test</td> <td>&gt; 0,8 N/mm<sup>2</sup></td> </tr> <tr> <td>Fire reactions</td> <td>NPD</td> </tr> <tr> <td>Dangerous substances</td> <td>Read the SDS</td> </tr> </table>		CO <sub>2</sub> permeability	NPD	Water vapour permeability	Class I	Capillary absorption and water permeability	< 0,1 kg*m <sup>-2</sup> *h <sup>-0,5</sup>	Direct traction adhesion test	> 0,8 N/mm <sup>2</sup>	Fire reactions	NPD	Dangerous substances	Read the SDS
CO <sub>2</sub> permeability	NPD												
Water vapour permeability	Class I												
Capillary absorption and water permeability	< 0,1 kg*m <sup>-2</sup> *h <sup>-0,5</sup>												
Direct traction adhesion test	> 0,8 N/mm <sup>2</sup>												
Fire reactions	NPD												
Dangerous substances	Read the SDS												

**DIASEN srl**

Zona Ind. Berbentina, 5 60041 Sassoferrato (AN) - ITALY  
 Tel. +39 0732 9718 - Fax +39 0732 971899 - [diasen@diasen.com](mailto:diasen@diasen.com) - [www.diasen.com](http://www.diasen.com)

PARTITA IVA 01553210426 - R.E.A. Ancona n.150933  
 Reg.Imp. Ancona 01553210426 - Cap. Soc. €400.000,00 i.v.

