

DECLARATION OF PERFORMANCE

CPR-U158

DP003EN22053101

- 1. Unique identification code of the product-type: Diathonite Screed
- 2. Intended use/es: Screed material for indoors and outdoors application in buildings.
- Manufacturer: Diasen SrI zona Ind.le Berbentina, 5 60041 Sassoferrato (AN) www.diasen.com
- 4. Systems of AVCP: System 4.
- 5. Harmonized standards: BS EN 13813:2002;

Notified bodies: No tasks for the notified body.

6. Performances declared:

Essential characteristics	Performances
Reaction to fire	Class A1 _{fl}
Flexural strength	> 2 F2
Compressive strength	> 10 C7
Thermal conductivity (λ _{10, dry})	0,060 W/m*K
Dangerous substances	See SDS

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by: **Diego Mingarelli (Legal Representative)** Sassoferrato, 22/11/2021

















Zona Industriale Berbentina, 5 – 60041 Sassoferrato (AN) – Italy
www.diasen.com

21

BS EN 13813:2002

DIATHONITE SCREED

Screed material for indoors and outdoors application in buildings

 $\begin{array}{lll} \mbox{Reaction to fire} & \mbox{Class A1}_{fl} \\ \mbox{Flexural strength} & > 2 \mbox{ F2} \\ \mbox{Compressive strength} & > 10 \mbox{ C7} \\ \mbox{Thermal conductivity } (\lambda_{10, \mbox{ dry}}) & 0,060 \mbox{ W/m·K} \\ \mbox{Dangerous substances} & \mbox{See SDS} \\ \end{array}$

DIASEN supplies the current annex along with the DoP to make the consultancy of the CE marking easier for the international clients. The enclosed CE marking can be slightly different compared to the one printed on the relevant packaging or documentation because of:

- graphic adaptations due to lack of space on the packaging or printing methods used,
- different language (the same packaging can be shared by several countries),
- the product is already in stock when the updating of the CE marking is implemented,
- printing mistakes.







